


Screw Terminal Board



DB-8225 Screw Terminal Board With CJC

Screw terminal board using 37-pin cable I/O ports for A-82X series and PCI-1800 series
 16-channel single-ended or 8-channel differential
 Blank pads for break detection, low-pass filter, current shut and voltage attenuation
 On board cold junction circuit in analog input channel 1 (Jumper selectable single-ended or differential mode)
 Dimensions: 114 mm x 170 mm


Ordering Information

Standard

- DB-8225/1:** Screw terminal board with CA-3710 cable
- DB-8225/2:** Screw terminal board with CA-3720 cable

Optional

- CA-3710:** 37-pin D-sub cable, 1m
- CA-3720:** 37-pin D-sub cable, 2m



DB-8125 Screw Terminal Board

DB-8125 is equipped with a DB-37 connector and two 20-pin flat-cable connectors
 Blank pads for break detection, low-pass filter, current shut and voltage attenuation
 Compatible to 880 series daughter board
 Dimensions: 221 mm x 115 mm


Ordering Information

Standard

- DB-8125:** Screw terminal board with CA-3710 cable

Optional

- CA-3710:** 37-pin D-sub cable, 1m
- CA-2020:** 20-pin flat cable, 2m
- CA-3720:** 37-pin D-sub cable, 2m



DB-1825 Screw Terminal Board

Screw terminal board using 37-pin cable I/O ports for PCI-1802, PCI-1002, PCI-1202, ISO-AD32 series
 32-channel single-ended, 16-channel differential
 Blank pads for break detection, low-pass filter, current shut and voltage attenuation
 Dimensions: 114 mm x 170 mm


Ordering Information

Standard

- DB-1825/1:** Screw terminal board with CA-3710 cable
- DB-1825/2:** Screw terminal board with CA-3720 cable

Optional

- CA-3710:** 37-pin D-sub cable, 1m
- CA-3720:** 37-pin D-sub cable, 2m



DB-8325 Screw Terminal Board

Screw terminal board using 37-pin cable for ISO-813 or other 813 series boards
 Blank pads for break detection, low-pass filter, current shut and voltage attenuation
 Dimensions: 220 mm x 114 mm

Ordering Information

Standard

- DB-8325/1:** Screw terminal board with CA-3710 cable
- DB-8325/2:** Screw terminal board with CA-3720 cable

Optional

- CA-3710:** 37-pin D-sub cable, 1m
- CA-3720:** 37-pin D-sub cable, 2m